



 PivotSystems™

Automated | Manual | Hydraulic

# Automated



The CS AutoPivot makes a stunning feature entrance way. The innovative design allows for oversized automated pivot doors. It has been engineered as a complete pivot door system designed to provide you with the ultimate in door luxury. Minimal door clearance and a simple adjustment method enable you to create a smooth, clean finish.

High quality components have been designed for all parts of the system, ensuring reduced servicing intervals and product longevity. The system is extremely flexible with a multitude of control settings and functions available.

It is supplied complete, with the top and bottom pivot gear pre-fitted to the door and the motor and gearbox installed within the supplied lintel.




**880lb**  
**400kg**

Max Door  
Weight



Optional  
Seals



Adjustable  
pivot point



Locking  
Options




Speed  
Adjustment



Range of  
Finishes



Operating  
Devices



**3"**  
**75mm**

Door  
Thickness

CS PivotSystems enable larger sizes than are typically available in traditional doors. Our high-performance hardware allows for smooth operation of panels much wider and taller than a traditional door.

The manual system is supplied complete with either a 1-1/2" or 3" (38mm or 75mm) aluminum door to suit the look of your project.


The pivot gear is hidden within the door, creating a subtle and stylish doorway.



Max Door Weight




Optional Seals



Adjustable pivot point



Range of Finishes



Door Thickness



Door Thickness

## Hydraulic

The hydraulic pivot system offers smooth closing with adjustable closing speed for both double and single action doors.


The majority of preparation can be accomplished prior to installation, leaving minimal on-site work. The pivot gear is factory fitted to a 1-1/2" (38mm) thick AluTec door and can be used for single or multiple doors.




Max Door Weight



Optional Seals



Adjustable pivot point




Hold Open 90° or 105°



Speed Adjustment



Range of Finishes



Door Thickness

© All copyright and other property in this document is reserved by Cavity Sliders USA Inc. Details and specifications are subject to change without notice. Whilst all care is taken to ensure the accuracy of all information, no responsibility will be accepted for any errors or omissions.  
**CS PIVOT SYSTEMS™** (O.D. 2018). 61296/US 04.2019

[www.cavitysliders.com](http://www.cavitysliders.com)

High quality  
products designed  
in New Zealand



T (888) 466 0030  
F (310) 769 5824  
E [info@cavitysliders.com](mailto:info@cavitysliders.com)

**Cavity Sliders USA Inc.**

548 Finney Ct  
Gardena  
CA 90248



 **CavitySliders™**  
The Pocket Door Experts