

Maintenance Checklist



Servicing of the CS AutoCav Residential should be carried out every 18 months.

Results can be recorded below.

A simple maintenance guide is given below. These checks should be integrated into a maintenance schedule.

Door Leaf

- 1 Check the carriages are running freely.
Wipe/clean the track if necessary.
- 2 Check the door has floor clearance, and runs clear of the floor guide.
- 3 If door seals are fitted check for excessive wear.

Door Controller

- 1 Ensure cables are free from the moving drive bar and belt.
- 2 Check and record cycle count on unit.
- 3 Check for loose plugs/terminals.

Door Motor

- 1 Ensure the motor mounts are secure.
- 2 Check for oil leaks.
- 3 Ensure belt and pulley is in good condition.
- 4 Check belt tension.

Door Operation

- 1 Check safety devices are operational.
- 2 Ensure the door and associated equipment are functioning correctly.

Date Checked						

Door Leaf							
1	Check the carriages are running freely. Wipe/clean the track if necessary.						
2	Check the door has floor clearance, and runs clear of the floor guide.						
3	If door seals are fitted check for excessive wear.						
Door Controller							
1	Ensure cables are free from the moving drive bar and belt.						
2	Check and record cycle count						
3	Check for loose plugs/terminals.						
Door Motor							
1	Ensure the motor mounts are secure.						
2	Check for oil leaks.						
3	Ensure belt and pulley is in good condition.						
4	Check belt tension.						
Door Operation							
1	Check safety devices are operational.						
2	Ensure the door and associated equipment are functioning correctly.						