

AutoCav™ Selection Chart

Features	Residential	Commercial
3½ or 3⅝" framing (90mm)	✓	✓
5½" framing (140mm)	✓	✓
Maximum door size	60" W x 96" H 1520 x 2438mm	60" W x 96" H 1520 x 2438mm
Maximum door weight - Single	220 lb 100kg	440 lb 200kg
Maximum door weight - Bi-Parting	130 lb 60kg	285 lb 130kg
High security lock		✓
Fire inputs		✓
Security system inputs		✓
Opening speed	16" - 20"/sec 400 - 500 mm/sec	1" - 23"/sec 20 - 600 mm/sec
Closing speed	4" - 20"/sec 100 - 500 mm/sec	1" - 23"/sec 20 - 600 mm/sec
Variable speed		✓
Force to open	✓	✓
Hold open	✓	✓
Partial open		✓
Fault monitoring		✓
Online commissioning		✓
4 inputs	✓	
6 inputs		✓
Home automation integration	✓	✓
UPS/Battery backup		✓
Safety Beams	✓	✓
Activation		
PDL switch	✓	✓
Overhead sensor	✓	✓
Handwave sensor	✓	✓
Multiple activation switches		✓
Configurable multi function button		✓
Secure mode programmable		✓
Wiring for PLC - Customer supplied activation	✓	✓

www.cavitysliders.com

High quality
products designed
in New Zealand



T (888) 466 0030
F (310) 769 5824
E info@cavitysliders.com

Cavity Sliders USA Inc.

548 Finney Ct
Gardena
CA 90248



CavitySliders™

The Pocket Door Experts